



WC-72-02-08	Quick Facts About Transferring Customer Molds			
Process Owner: Engineering / Quality		Effective Date: 8/3/2015	Rev. A	Pg. 1 of 1
Approved: 8/3/2015 3:58 PM - Jim Tarsinos				

Mold Evaluation

- We will qualify your tooling before beginning production.
- If your tooling is worn or damaged, we can do most mold repairs or modifications inhouse preventing inconvenient downtime.
- Our <u>Customer Furnished Tooling Policy</u> contains complete details about transferring preexisting tooling to JET Rubber, Inc.

Molding

- We can compression mold tooling up to 48 inches in diameter.
- We can transfer mold up to 24 inches in diameter.
- We are able to bond most elastomers to most grades of metal or plastic.

Material

- We have elastomers that meet most Oilfield, ASTM or Military specifications and can help develop new formulations when necessary.
- We test and verify all elastomer compounds to their respective ASTM D2000 requirements.
- We store only verified elastomers in a temperature-controlled <u>storage area</u> that is electronically monitored to email noncompliant temperature notifications.

Storage

- We store our customer molds as if they belonged to us.
- We understand why it is called a **mold bank**, and we are going to **protect your investment**.
- To demonstrate the respect you have made in your tooling investment, we have invested in the fabrication of <u>Appropriate</u> and <u>Adequate Mold Storage Areas</u> to protect and to safely store your tooling.
- We maintain our mold inventory in an electronic database.
- We indentify all molds with heat-resistance markers and bar code labels.

I am interested about moving my molds, please contact me.